





Specifications

Boat Details

Price POA Boat Brand Yamaha Model F50 Length 0.00

Year 2024 Category Boat Engines and Outboards


Hull Style

Power Type Power Stock Number F50LB

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.

Hull Type





Condition Suburb New ERMINGTON State Engine Make **New South Wales**

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Description

With a sleek low-profile cowling design, matched with a silky-smooth four-cylinder engine configuration, inside of a compact and light-weight body, the F50 looks as good as it performs.

Within the F50 is a proven single overhead cam, 996cc, four-cylinder marine engine, that delivers an excellent power-to-weight ratio and exceptional refinement and fuel-efficiency. Out of the entire 4-cylinder 50 horsepower category, the F50 is the only Japanese manufactured engine in its class; which translates to superior reliability, refinement and quality that Yamaha engines are renowned for.

Utilising Yamaha's exclusive Multi-Point Fuel Injection System (EFI) and Electronic Control Module (ECM), the F50 delivers impressive power and torque, smooth and comfortable operation, low noise levels and emissions, and the best fuel-economy in its class.

The 50 horsepower is now available in both signature Yamaha grey and new pearlescent white colour options.

Technical Specification HeightL: 527 [20.7] WeightL: 113

Engine4-Stroke, SOHC In-line 4

Displacement996.0

Bore65 x 75

Max RPM5000-6000 LubricationWet-sump

FuelEFI IgnitionTCI StarterElectric

Alternator12V - 16A with rectifier regulator

OperationMechanical Control (Optional Tiller Handle Available)

TiltPower Trim & Tilt GaugesOptional Network GaugesOptional Gear Ratio1.85: 1

Engine Details

Horse Power

50

Disclaimer